

Technical Data Sheet

AF-816

Ingredient	Silicone oil and hydrophobic particles of water emulsion
Warranty	6 months (kept in a cool, dry place at room temperature)
Applications	AF-816 is used in
	 Added to textile printing and dyeing process
	 Add printing and dyeing auxiliaries
Features	Good compatibility with the system
	 Good defoaming and defoaming
	performance under low dosage
	 Suitable for a variety of foaming
	environments

Physical indicators

Exterior White or yellowish milky liquid

Solid content (≥48) %

pH value 6.0-9.0

Viscosity, 25°C 2000-10000mPa.s



Instructions

- It can be used directly or diluted to a low content.
- Can be diluted directly with water, but need to be used immediately, if the dilution needs to be stored for a certain time, you can consult our company, our company will provide professional dilution method.
- The addition amount is generally 10~1000ppm, and the optimal addition amount is determined according to the actual situation on site.

Precautions

- There are no fatal or harmful ingredients to the human body, but try not to touch it directly or use it if it accidentally gets into the eyes, rinse with clean water
- Storage at room temperature (5-40°C), away
 from direct sunlight
- Refer to the product's Material Safety Data
 Sheet (MSDS) before use

Usage

• Not for human injection

restrictions

• This product is not tested or represented as suitable for medical or pharmaceutical use



Package

• 25kg/200kg plastic drum or 1000kg IBC

drum

LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information provided here is believed to be accurate and in good faith. However, because conditions and methods of use of our products are beyond our control, this information should not substitute for customer's testing to ensure that our products are safe, effective, and fully satisfactory for their intended use. Suggestions for use shall not be construed as grounds for infringement of any patent rights.