

Technical Data Sheet

AF-900

Ingredient	Silicone oils, hydrophobic particles and
	synergists
Warranty	6 months (kept in a cool, dry place at room
	temperature)
Applications	AF-900 is used in
	 Industrial water treatment
	 Textile additives
	Water-based ink
Features	• The bubble inhibition ability is outstanding
	 Good acid and alkaline resistance
	 Good compatibility with the system
Physical indicators	
Exterior	White or yellowish milky liquid
Viscosity, 25℃	C 500~2000mPa.s
Instructions	• Directly added use, can also be diluted to low
	content use.
	• Can be diluted directly with water, but need
	to be used immediately, if the dilution needs



to be stored for a certain time, you can consult our company, our company will provide professional dilution method.

- Add 100~1000ppm.
- The optimal addition amount depends on the actual situation on site.

Precautions

- There are no fatal or harmful ingredients to the human body, but try not to touch it directly or use it if it accidentally gets into the eyes, rinse with clean water
- Storage at room temperature (5-40°C), away
 from direct sunlight
- Refer to the product's Material Safety Data
 Sheet (MSDS) before use

Usage

Not for human injection

restrictions

 This product is not tested or represented as suitable for medical or pharmaceutical use

Package

25kg/200kg plastic drum or 1000kg IBC
 drum

LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information provided here is believed to be accurate and in good faith. However, because conditions and methods of use of our products are beyond our control, this information should not substitute for customer's testing to ensure that our products are safe, effective, and fully satisfactory for their intended use. Suggestions for use shall not be construed as grounds for infringement of any patent rights.